215KWH All-in-one Liquid Cooling BESS























>>> Features

Easy installation, operation and maintenance

Highly integrated, convenient for transportation, operation and maintenance

Fully pre-assembled, no need for on-site installation o battery modules

Fully functional debugging, meets the requirements for many scenarios with simple configurations available for use

User-Friendly

Intelligence Remote support for strategy adjustments, configuration, and data viewing

Real-time status monitoring and fault logging, Enables fault warning and location identification

Built-in battery performance monitoring and recording capabilities

Seamless Switching

Grid and off-grid switching time is less than 20 ms, allowing for uninterrupted load switching

Long Operating Life, Support Full Power charge and discharge

Intelligent liquid cooling ensure higher efficiency

Intelligent liquid cooling prolongs battery life

Battery cells operate in an environmentally friendly manner, ensuring charge and discharge power

Safe and Reliable

Multi-level protection for AC and DC, the system quickly disconnects during anomalies

Fire detection and protection at PACK level and cluster level, effectively managing dual detection in battery and electrical compartments for comprehensive coverage

Flexible Configuration

Supports multiple Ongrid parallel Support 0.5C and 1C charging/discharging Support On/Off grid parallel

Compatible with diesel generation, wind power, photovoltaic systems, and uninterrupted switching

Technical Specification for 2 hours Backup (0.5C)

| MODEL | 100KW-215KWH | 100KW-232KWH | 125KW-241KWH | 125KW-252KWH | 125KW-261KWH | | | |
|---|---|---------------------------|---|-----------------------|--------------------|--|--|--|
| DC(Battery) | | | | | | | | |
| Cells Type | | LiFeP | O4 Lithium Iron Phos | phate | | | | |
| Cell specfication | 3.2V28OAh | 3.2V28OAh | 3.2V314Ah | 3.2V304Ah | 3.2V314Ah | | | |
| Configuration of Battery | 240S1P | 260S1P | 240S1P | 260S1P | 260S1P | | | |
| Battery Capacity | 215kWh | 232kWh | 241kWh | 252kWh | 261kWh | | | |
| Max. Power | 100KW | 100KW | 100KW | 100KW | 100KW | | | |
| Max. Current | 140A | 140A | 157A | 152A | 157A | | | |
| Battery Rated Voltage | 768V | 832V | 768V | 832V | 832V | | | |
| Battery Voltage Range | 672V-864V | 728V-936V | 672V-864V | 728V-936V | 728V-936V | | | |
| AC(On / Off Grid) | | | | | | | | |
| Max. Power(kVA) | 110KVA | | 137KVA | | | | | |
| Active Power(kW) | 100KW | | 125KW | | | | | |
| Rated Voltage(V) | 400V | | 400V | | | | | |
| Rated Current(A) | 144A | | 180A | | | | | |
| Voltage Range | 320V-460V | | 320V-460V | | | | | |
| Rated Frequency | 50/60Hz | | 50/60Hz | | | | | |
| Range of Frequency | 45-55/55-65Hz | | 45-55/55-65Hz | | | | | |
| THDI | <39 | <3% | | <3% | | | | |
| Power factor | 1.0(Adjustable from 0.8 leading to 0.8 lagging) | | 1.0(Adjustable from 0.8 leading to 0.8 lagging) | | | | | |
| AC System | | 3 phase 4 wires | | 3 phase 4 wires | | | | |
| Overload capability | 110% | | | | | | | |
| Solar Side(PV) | | | Optional | | | | | |
| Max. Power | 100KW(50KW*2) | | | | | | | |
| High Volage side Voltage | 560V-1000V | | | | | | | |
| High Voltage side Current | 160A | | | | | | | |
| Low Voltage side Voltage | 500V-900V | | | | | | | |
| Low Voltage side Voltage | 200A | | | | | | | |
| Uninterrupted Load(STS) | Optional | | | | | | | |
| STS Power | 200KW | | | | | | | |
| STS Voltage | 400V 50HZ/60HZ | | | | | | | |
| Overload Poer | 110% | | | | | | | |
| Shift Time | <20mS | | | | | | | |
| System operation stratege | | | 1201110 | | | | | |
| Functional | Anti Backflow and Black Start | | | | | | | |
| Operation Mode Selections | | | | | | | | |
| operation mode objections | photovoltaic priority for electricity cost savings, wind power generation | | | | | | | |
| | priority for electricity cost savings, wind power generation priority for electricity cost savings, wind power generation | | | | | | | |
| Scienerios | Photovaltaic and diesel storage project, Wind power and diesel storage project, Wind and photovoltaic | | | | | | | |
| | diesel storage project, Charging Station + Energy storage project, On-grid electricity selling project | | | | | | | |
| Specificaiton | dicoor otorage | orojoot, oriarging otatio | ir Energy otorage pr | oject, en gna cicetne | ity coming project | | | |
| Cabinet Size(W*D*H) | | | 1585/1366/2055mm | | | | | |
| Weight | • | | | | | | | |
| Max. cycle efficiency | ≤2.7 T | | | | | | | |
| Protection | ≥ 90% IP55 | | | | | | | |
| Auxiliary Power Supply | IP55 Solf powered Externally powered | | | | | | | |
| | Self-powered, Externally powered | | | | | | | |
| Corrosion resistance rating | | | | | | | | |
| Operating Temperature | | | | | | | | |
| Operating Temperature Max Operation Altitude | -30 -50 (>45 derating) | | | | | | | |
| Max. Operation Altitude | 2000 m | | | | | | | |
| Cooling method | Intelligency Liquid Cooling | | | | | | | |
| Fire safety configuration | Smoke detector, Heat detector, Gas-based fire extinguishing system, | | | | | | | |
| | Pressure relief valve, Pack-level fire protection, | | | | | | | |
| 0 | Cluster-level fire protection, Water-based fire protection, Automoatic pressure relief | | | | | | | |
| Communication | | Ethernet 485 CAN | | | | | | |
| Communication Protocal | ModbusTCP | | | | | | | |

Technical Specification for 1 hours Backup (1C)

| MODEL | 200KW-215KWH | 200KW-232KWH | 200KW-241KWH | 250KW-252KWH | 250KW-261KWH | | |
|-----------------------------|--|-----------------|---|-----------------|--------------|--|--|
| DC(Battery) | | | | | | | |
| Cells Type | | l iFeP | O4 Lithium Iron Phos | phate | | | |
| Cell specfication | 3.2V28OAh | 3.2V28OAh | 3.2V314Ah | 3.2V304Ah | 3.2V314Ah | | |
| Configuration of Battery | 240S1P | 260S1P | 240S1P | 260S1P | 260S1P | | |
| | 215kWh | 232kWh | 240311 241kWh | 252kWh | 261kWh | | |
| Battery Capacity | 100KW | 200KW | | 250KW | 250KW | | |
| Max. Power | | | 200KW | | | | |
| Max. Current | 280A | 280A | 314A | 304A | 280A | | |
| Battery Rated Voltage | 768V | 832V | 768V | 832V | 832V | | |
| Battery Voltage Range | 672V-864V | 728V-936V | 672V-864V | 728V-936V | 728V-936V | | |
| AC(On / Off Grid) | | | | | | | |
| Max. Power(kVA) | 110KVA | | 137KVA | | | | |
| Active Power(kW) | 100KW | | 125KW | | | | |
| Rated Voltage(V) | 400V | | 400V | | | | |
| Rated Current(A) | 288A | | 360A | | | | |
| Voltage Range | 320V-460V | | 320V-460V | | | | |
| Rated Frequency | 50/60Hz | | 50/60Hz | | | | |
| Range of Frequency | 45-55/55-65Hz | | 45-55/55-65Hz | | | | |
| THDI | <3% | | <3% | | | | |
| Power factor | 1.0(Adjustable from 0.8 leading to 0.8 lagging) | | 1.0(Adjustable from 0.8 leading to 0.8 lagging) | | | | |
| AC System | 3 phase 4 | 3 phase 4 wires | | 3 phase 4 wires | | | |
| Overload capability | 110% | | | | | | |
| Solar Side(PV) | | | Optional | | | | |
| Max. Power | 100KW(50KW*2) | | | | | | |
| High Volage side Voltage | 560V-1000V | | | | | | |
| High Voltage side Current | | | | | | | |
| Low Voltage side Voltage | 500V-900V | | | | | | |
| Low Voltage side Voltage | 200A | | | | | | |
| Uninterrupted Load(STS) | | | | | | | |
| STS Power | Optional 200KW | | | | | | |
| | 200KW 400V 50H7/60H7 | | | | | | |
| STS Voltage Overload Poer | 400V 50HZ/60HZ | | | | | | |
| | 110% | | | | | | |
| Shift Time | | | <20mS | | | | |
| System operation stratege | | Λ 4.* | Dealdless and Disale | VI I | | | |
| Functional | Anti Backflow and Black Start | | | | | | |
| Operation Mode Selections | | | | | | | |
| | photovoltaic priority for electricity cost savings, wind power generation | | | | | | |
| | priority for electricity cost savings, off grid power supply for remote areas | | | | | | |
| Scienerios | Photovaltaic and diesel storage project, Wind power and diesel storage project, Wind and photovoltaic | | | | | | |
| | diesel storage project, Charging Station + Energy storage project, On-grid electricity selling project | | | | | | |
| Specificaiton | | | | | | | |
| Cabinet Size(W*D*H) | 1585/1366/2055mm | | | | | | |
| Weight | ≤2.7 T | | | | | | |
| Max. cycle efficiency | ≥ 90% | | | | | | |
| Protection | IP55 | | | | | | |
| Auxiliary Power Supply | Self-powered, Externally powered | | | | | | |
| Corrosion resistance rating | C3/C5 | | | | | | |
| Operating Humidity Range | 0%-100%(Non-condensing) | | | | | | |
| Operating Temperature | -30 -50 (>45 derating) | | | | | | |
| Max. Operation Altitude | 2000 m | | | | | | |
| Cooling method | Intelligency Liquid Cooling | | | | | | |
| Fire safety configuration | Smoke detector, Heat detector, Gas-based fire extinguishing system, | | | | | | |
| rife safety configuration | Pressure relief valve, Pack-level fire protection, | | | | | | |
| | | | | | | | |
| Communication | Cluster-level fire protection, Water-based fire protection, Automoatic pressure relief | | | | | | |
| Communication Protocol | Ethernet 485 CAN | | | | | | |
| Communication Protocal | ModbusTCP | | | | | | |

Note: Some spare parts are available. For details, please consult with our sales for further communication.